



## Fire sleeve - F88 VIGOSIL

The cost-effective, round-dipped fire sleeve with silicone coating.

**Certifications**      DIN EN 45545-2:2020 R22/R23-HL3  
ISO 15540:2016

### Technical data

**Backing material**      ISO 2078 mineral fibre, Woven fabric up to DN40,  
knitted fabric up to DN100

**Coating**                Silicone - ISO 1629/LSR

**Temperature Range**    Continuous temperature: -60 to +300 °C  
Short-term with fire exposure up to 1200 °C  
Short-term partial overheating up to 1600 °C

**Technical values**      Wall thickness: 3,0 - 4,0 mm  
Weight: 4,5 kg/m<sup>2</sup>

**Available sizes**        Available lengths 40 m up to DN40,  
25 m up to DN100

### Key characteristics

- excellent mechanical protection
- halogen-free flame protection
- free of softeners
- free of heavy metals
- REACH-compliant

### Product details

DN	product number	approx. weight g/m
6	4448 8 006	204
8	4448 8 008	228
10	4448 8 010	249
13	4448 8 013	262
15	4448 8 015	281
20	4448 8 020	304
22	4448 8 022	321
25	4448 8 025	342
30	4448 8 030	394
32	4448 8 032	416
35	4448 8 035	436
38	4448 8 038	450

DN	product number	approx. weight g/m
40	4448 8 040	461
44	4448 8 044	492
50	4448 8 050	438
57	4448 8 057	581
60	4448 8 060	610
65	4448 8 065	740
70	4448 8 070	800
75	4448 8 075	895
80	4448 8 080	1215
90	4448 8 090	1367
100	4448 8 100	1418

